



General

- Manufactured to BS 7671 (IET Wiring Regulations 17th Edition)
- Certificate of Portable Appliance Testing (PAT) to BS 7671 (IET Wiring Regulations 17th Edition)
- Overall cable diameter: 14mm
- Cable length: 2m
- RoHS Compliant
- Toroidal Choke on earth conductor

Conductors

- Fine copper wire strands produced to BS6360 Class 5
- 50 copper strands per core
- Three cores of 2.5mm² each produced to BS60228 and IEC60228
- Cores are colour coded to HD308 S2

Insulation

- Triple-insulated with PVC
- Steel braiding to minimise interference and protect the cable against damage
- Outer sheath is transparent

Appliance Plug

- IEC C13 appliance plug, manufactured to IEC 60320
- Perma-Lock™ Terminals so that heat and vibration cannot loosen the screws
- Heavy Duty Vinyl Connector Body
- UL Listed 309E
- CSA Listed
- Contacts cryogenically treated (frozen to approximately -150°C) to de-stress the metal
- Colour: Black

Mains Plug

- UK 13A Mains Plug manufactured to BS 1363
- ASTA Listed
- Base: Urea Formaldehyde
- Cover: PVC
- Contacts: Sleeved brass pins, phosphor bronze clips
- 13A (BS 1362) fuse
- Colour: Black

Operation

- Operating temperature from -5°C to +70°C
 - Bend radius when static is 10 x cable diameter
-

Argonaught New Technology
9 Dunmow Road, Thaxted
Essex, CM6 2LU, UK

www.antaudiosolutions.co.uk