



---

## General

- Manufactured to BS 7671 (IET Wiring Regulations 17th Edition)
- Certificate of Portable Appliance Testing (PAT) to BS 7671 (IET Wiring Regulations 17th Edition)
- Overall cable diameter: 8mm
- Cable length: 2m
- RoHS Compliant

## Conductors

- Fine 99.9% OFC copper wire strands produced to BS6360 Class 5
- 42 copper strands per core
- Six cores of 0.75mm<sup>2</sup> each produced to BS60228 and IEC60228

## Insulation

- Insulated with transparent PVC
- Outer sheath is braided polyester

## Appliance Plug

- IEC C13 appliance plug, manufactured to IEC 60320
- Perma-Lock™ Terminals so that heat and vibration cannot loosen the screws
- Heavy Duty Vinyl Connector Body
- UL Listed 309E
- CSA Listed
- Contacts cryogenically treated (frozen to approximately -150°C) to de-stress the metal
- Colour: Black

## Mains Plug

- UK 13A Mains Plug manufactured to BS 1363
- ASTA Listed
- Base: Urea Formaldehyde
- Cover: PVC
- Contacts: Sleeved brass pins, phosphor bronze clips
- 13A (BS 1362) fuse
- Colour: Black

## Operation

- Operating temperature from -5°C to +70°C
  - Bend radius when static is 10 x cable diameter
- 

**Argonaught New Technology**  
9 Dunmow Road, Thaxted  
Essex, CM6 2LU, UK

[www.antaudiosolutions.co.uk](http://www.antaudiosolutions.co.uk)